



ENGINE	
Type	Air cooled, 4 - stroke single cylinder OHC, Self start
Displacement	149.2 cc
Maximum Power	9.7 kW (13.2 Ps) @ 7500 rpm
Maximum Torque	13.4 N-m @ 5000 rpm
Ignition	D.C - CDI Ignition System
Gears	5 Speed constant mesh
FRAME	
Type	Semi-double cradle
Wheel Base	1360 mm
Ground Clearance	245 mm
Tyre Size (Front)	90 / 90 x 19 - 52 P
Tyre Size (Rear)	110 / 90 x 17- 60 P
Fuel Tank capacity	11.1 Litre (Min) - 2.6 Litre (Usable reserve)
SUSPENSION	
Front	Telescopic Hydraulic Shock Absorbers
Rear	Swing Arm with Mono Suspension with Nitrox
Brakes -Front	Dia 240 mm Disc
Brakes -Rear	Internal expanding shoe type (110 mm)
ELECTRICAL	
Headlight	12 V - 35 W / 35 W - Halogen Bulb (Multi-Reflector Type)
Battery	12V - 4 Ah, MF Battery
Tail / Stop Lamp	12V - 0.5 W / 4.1 W LED LAMP
Turn Signal Lamp	12 V- 10 W (Amber Bulb) x 4 nos (Multi- Reflector - Clear Lens)



THIS REVOLUTIONARY TECHNOLOGY MOVES THE AIR AND PETROL MIXTURE WITHIN THE COMBUSTION CHAMBER IN A WHIRLING MOTION IN ORDER TO IMPROVE COMBUSTION. THIS PROVIDES FOR THE BEST BALANCE OF POWER AND FUEL EFFICIENCY. HENCE, MORE MILEAGE AND LESS POLLUTION.



Accessories and features shown may not be a part of the standard fitment. It is our endeavour to constantly improve our products. This could lead to changes in product specifications without notice. Hero Impulse complies with BS III norms. *Warranty for a period of 3 years or 40,000 kms from the date of purchase, whichever is earlier.

Hero MotoCorp Ltd.
34, Community Centre,
Basant Lok, Vasant Vihar, New Delhi 110057
Phone: 011-46044100, 26142451
Fax: 011-26143321, 26143198
www.heromotocorp.com

