

RIDE THE FUTURE



GLAMOUR

**PGMI
FI**

PROGRAMMED FUEL INJECTION

PGM-FI

PROGRAMMED FUEL INJECTION

PGM-FI works by injecting the appropriate amount of fuel into the cylinder, precisely calculated from the data received through high tech sensors in the engine that feeds the engine data and environmental conditions to a central computer system called the ECU - Electronic Control Unit. Based on the data received from the sensors, the ECU decides the quantity and timing of fuel to be injected through the fuel injector. Thus the PGM-FI system offers excellent drivability, optimum fuel efficiency, lower emission and instant start even in extreme ambient temperature conditions and at higher altitudes.

HERO HONDA

TECHNOLOGY THAT KEEPS ME DRIVING



PGM-FI enhances engine response and reduces knocking and frequent gear change

TECHNOLOGY THAT KEEPS ME EFFICIENT



Real Time Mileage Indicator displays the actual average mileage for preceding 10 seconds

TECHNOLOGY THAT KEEPS ME SAFE



Bank Angle Sensor switches off engine automatically if the bike tips over

SPECIFICATIONS

ENGINE

Type	Air cooled, 4 - stroke single cylinder OHC
Displacement	124.8 cc
Maximum Power	6.72 kW (9 bhp) @ 7000 rpm
Maximum Torque	10.35 N-m @ 4000 rpm
Bore x Stroke	52.4 x 57.9 mm
Compression Ratio	9.2:1
Fuel System	Electronic Fuel Injection (PGM-FI)
Ignition System	DC - FTI - D.C Fully Transistorised Ignition
Starting	Self Start / Kick Start

TRANSMISSION

Clutch	Multiplate wet
Gear box	4 Speed constant mesh

CHASSIS

Type	Tubular Double cradle type
------	----------------------------

SUSPENSION

Front	Telescopic Hydraulic Shock Absorbers
Rear	Swing Arm with Hydraulic Shock Absorbers

BRAKES

Front	Disc	240 mm Dia. Pad - Non Asbestos type
	Drum	Internal expanding shoe type - 130 mm Liners - Non Asbestos type
Rear	Drum	Internal expanding shoe type - 130 mm Liners - Non Asbestos type

WHEELS AND TYRES

Rim Size	Front	18 x 1.60, Cast Wheel
	Rear	18 x 1.60, Cast Wheel
Tyre Size	Front	2.75 x 18 - 42 P / 4 PR
	Rear	3.00 x 18 - 52 P / 6 PR

ELECTRICALS

Battery	12 V - 3 Ah MF Battery
Head lamp	12 V - 35 W / 35 W - Halogen Bulb, (MFR)
Tail / Stop lamp	12 V - 5 / 21 W (MFR)
Turn signal lamp	12 V - 10 W (Amber Bulb) x 4 nos (MFR - Clear Lens)

SERVICE DATA

Engine oil grade	SAE 10 W 30 SJ Grade
Fuel Tank capacity	12 litre (Min)
Reserve	1.5 litre (Approx.)

DIMENSIONS

LxWxH	2005 X 735 X 1070 mm
Wheelbase	1265 mm
Ground clearance	150 mm

WEIGHTS

Kerb weight	125 Kg (Kick) / 129 Kg (Self)
-------------	-------------------------------



Colours Available



BLACK WITH SPORTS RED



SHIELD GOLD METALLIC



CANDY BLAZING RED



Edgy new Visor and Headlight



New Digital Analog Combo Meter Console



Stunning new Graphics

GLAMOUR

PGM-FI

Accessories shown may not be a part of standard equipment. It is our endeavour to constantly improve our products. This could lead to changes in product specifications without notice. Hero Honda Glamour PGM-FI complies with BS III emission norms. Shown above is an indicative picture of PGM-FI. Warranty for a period of 3 years or 40,000 kms from the date of purchase, whichever is earlier. Hero Honda Motors Ltd., 34, Basant Lok, Vasant Vihar, New Delhi-110057, Phone: 011-46044100, Fax: 011-26143321,26143198

